



Technical Data Sheet:


07.2022




Product Details:

Product Name:	Fibreglass Body Filler
Product Description:	<p>Germa-Tech Fibreglass filler is a fast drying fibreglass filler with great adhesion and perfect tension.</p> <p>Ideal for restoring cracks or broken panels.</p>

Substrates:

	<p>Sanded galvanised steel, sanded aluminium, sanded steel or epoxy primer.</p> <p>Not Suitable For: Thermoplastic paint, Plastic Primer, Etch Primer</p>
---	--

Surface Preparation:

	<p>Remove Wax, Silicon and other contaminants with Germa-Tech Prepsol and Germa-Tech Prepsol wipes.</p>
---	---


Directions For Use:
Mixing Ratio:


Body Filler: Hardener = 50:1 (by weight) do not over harden.

Thoroughly mix, avoid stirring air into mix

WARNING

Always knead BPO hardener before use
Always stir filler can before pouring from can

Pot Life:

Application Life at 25 °C

3-5 Minutes

Shelf Life

Shelf Life is up to 36 months if unopened and stored in a cool dry place (below 20°C). Shelf life is an optimal guide and the product is manufactured and tested to exceed shelf life recommendations, avoid ambient temperatures above 20 and exposure to direct sunlight which are amongst common factors that will diminish storage shelf life. Contact the distributor or manufacturer if requiring further advice.

If stored correctly, it can be used for up to 12 months from opening the original seal

Drying Time:


Gel Time	3-5 Minutes at 25°C
Wet-Sanding	9 Minutes at 25°C
Dry-Sanding	20 Minutes at 25°C

allow additional drying times in colder weather

Sanding Grit:


Germa-Tech P80 - P180-P240

Additional Information
Density (g/cm3):

1.7

The information contained in this file is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.