

SOFTENING AGENT FLEX AID



Technical Data Sheet:

01.2024



Product Details:	GP-5112
Product Name:	Softening Agent – Flex Aid
Product Description:	<p>Germa-Tech Softening Agent is specially designed for soft or flexible substrates to improve the softness of the basecoat and topcoat.</p> <p>Reduces paint imperfections in flexible, deformed and soft substrates.</p>

Usage:



Basecoat - 2K Solid Colours & Clear Coats.

Directions For Use:

Mixing Ratio:



1. 10-30% Softening Agent into 2k paint depending on the flexibility of the substrate
2. 10% Softening Agent into basecoat or 1k primer.
3. Add hardener or thinners per normal mixing procedures for the paint

Pot Life:

Pot Life of paint mixed with Softening Agent will not be altered, refer paint mix pot life



Additional Information

Notes:	Recommended addition of Softening Agent is no more than 30%
Storage:	Store in a cool dry place. Always replace the lid securely after use.
Shelf Life:	<p>Shelf Life is up to 48 months if unopened and stored in a cool dry place (below 20°C). Shelf life is an optimal guide and the product is manufactured and tested to exceed shelf-life recommendations, avoid ambient temperatures above 20°C and exposure to direct sunlight which are amongst common factors that will diminish storage shelf life. Contact the distributor or manufacturer if requiring further advice.</p> <p>If stored correctly, it can be used for up to 12 months from opening the original seal</p>

The information contained in this file is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.