



## Technical Data Sheet:


07.2022




### Product Details:

<b>Product Name:</b>	Prepsol Degreaser
<b>Product Description:</b>	<p>Germa-Tech prepsol is able to remove grease, oil, and other surface contaminants to avoid paint film defects.</p> <p>Use with Germa-Tech prepsol wipes.</p>


### Substrates:

	Existing finishes, Primers, Putty, and Metals
---	---

### Directions For Use:

	<p>Use over bare metal before the application of primers. Also use regularly after sanding and before applying topcoat. Use a clean cloth and apply to the surface. Wipe small areas with a Germa-Tech Prepsol wipe, then dry with a separate clean wipe. Do not allow Prepsol to dry on the surface.</p>
---	---

**Additional Information**

<b>Mixing Ratio:</b> 	Ready for use.
<b>Storage:</b>	Store in a cool dry place. Always replace the lid securely after use.
<b>Shelf Life:</b>	<p>Shelf Life is up to 48 months if unopened and stored in a cool dry place (below 20°C). Shelf life is an optimal guide and the product is manufactured and tested to exceed shelf life recommendations, avoid ambient temperatures above 20 and exposure to direct sunlight which are amongst common factors that will diminish storage shelf life. Contact the distributor or manufacturer if requiring further advice.</p> <p>If stored correctly, it can be used for up to 12 months from opening the original seal</p>
<b>Packaging:</b>	5L - 4 cans per box 1lt - 12 cans per box

*The information contained in this file is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.*