

## ANTI SILICON





## Technical Data Sheet:

07.2022



Product Details:	
Product Name:	Anti Silicon
Product Description:	<b>Germa-Tech Anti Silicon is an additive</b> for 2k solid colours or clear coats, able to remove fisheyes or cratering on the paint film.

Substrates:	
	2K Solid colours and Clear Coats.

Directions For Use:		
Application:	Spray one or two coats over the paint film with fisheyes or craterings by paint mixed with Anti Silicon.	
Mixing Ratio:	Paint ready for use: Anti Silicon = 1L: 0.5-2 tin cap (about 4-15g)	

Technical Data Sheet







Additional Information	
Storage:	Store in a cool dry place. Always replace the lid securely after use.
Shelf Life:	Shelf Life is up to 48 months if unopened and stored in a cool dry place (below 20°c). Shelf life is an optimal guide and the product is manufactured and tested to exceed shelf life recommendations, avoid ambient temperatures above 20 and exposure to direct sunlight which are amongst common factors that will diminish storage shelf life. Contact the distributor or manufacturer if requiring further advice.  If stored correctly, it can be used for up to 12 months from opening the original seal
Packaging:	250ML*12 cans per box
Notes:	<ol> <li>Mix with the right ratio of Anti Silicon. Excess addition may cause defects of small bubbles or pinholes.</li> <li>In serious problems, fisheye affected paint film must be sanded out and filled when it is hard dry. Refinish with paint mixed with Anti Silicon.</li> </ol>

The information contained in this file is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.

